

SCUDO WPC

Hydro and oil repellent protective product for WPC. Outdoor Line



Description

SCUDO WPC is a specific product developed with high penetrating nanotech particles for the protection and treatment of WPC, precompressed woods and other composites materials. SCUDO WPC increases the water and oil resistances of the treated surfaces, avoiding the formation of unaesthetic and persistent stains due to the absorption of oils and dirt. It gives a slight toning effect.

Characteristics

Mixture ratio	single-component
Appearance	liquid
Application temperature	+10°C ÷ +25°C
Application	brush / spray
Coverage	1 L / 14 m ² (depending on the porosity and the absorption of the compound)
Painting over	>10 h ⁽¹⁾
Complete hardening	12/24 h ⁽¹⁾
Storage stability	1 year ⁽²⁾
Packaging	1 L - 5 L
Tool cleaning	DILUENTE DNE

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Clean the surface before applying SCUDO WPC by brush. It is recommended to use PULITORE INTENSIVO WPC or WPC SPRAY CLEAN (see relative TDS).

Apply one coat of SCUDO WPC spreading it well on the surface. After 10 hours and anyway after total drying apply a second coat without sanding. Do not leave puddles and spread the product well. During the application there could be some foam which will disappear without changing final look.

Apply the product with stable weather conditions avoiding too high temperatures.

Notes

In order to avoid liquid absorption it is always recommended to maintain and restore the treatment frequently.

Even if surface is treated with SCUDO WPC or SCUDO WPC COLOR RESTORE the color can slightly change in time due to the strong sun action.

Label elements

· Flammable liquid and vapour.· May be fatal if swallowed and enters airways.· May cause an allergic skin reaction.· May cause drowsiness or dizziness.· Harmful to aquatic life with long lasting effects.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Wear protective gloves / protective clothing / eye protection / face protection.· IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.· DO NOT induce vomiting.· In case of fire: use water to extinguish.

Contents:HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS; (R)-P-MENTHA-1,8-DIENE; HYDROCARBONS C11-C14 N-ALCANI, ISOALCANS, CYCLES <2% AROMATIC ;



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_SCUDO_WPC.pdf